

This chart is based on dimensions used by Core Engineered Solutions. When using these charts please take into consideration that fuel volume will change approximately .5% for every 10 degrees F change in fuel temperature.



CONVAULT MM-TO-LITER CONVERSION CHART
1900 LITERS (500 U.S. GALLON) - DOUBLE WALL STEEL

(dimensions are mm)	Length	Width	Height
External Dimensions	3353	1372	1016
Internal Dimensions			
1900 LITERS	3038	1041	600

mm	Liters	mm	Liters
1	3.3	270	854
2	6.3	280	886
3	9.5	290	918
4	12.7	300	949
5	15.8	310	981
6	19.0	320	1013
7	22.1	330	1044
8	25.3	340	1076
9	28.5	350	1107
10	18	360	1139
20	36	370	1171
30	55	380	1202
40	73	390	1234
50	91	400	1266
60	109	410	1297
70	128	420	1329
80	146	430	1361
90	164	440	1392
100	182	450	1424
110	201	460	1456
120	219	470	1487
130	237	480	1519
140	255	490	1550
150	273	500	1582
160	292	510	1614
170	310	520	1645
180	328	530	1677
190	346	540	1709
200	365	550	1740
210	383	560	1772
220	401	570	1804
230	419	580	1835
240	438	590	1867
250	456	600	1899
260	474		