

TANK CALIBRATION CHART

Core Engineered Solutions

Tank type: Horizontal Cylindrical UL-2085  
 Tank nominal capacity: 6,000 gallons  
 Diameter: 82.00 inches  
 Length 264 inches

<u>Depth</u> (inches)	<u>Capacity</u> (gallons)	<u>Depth</u> (inches)	<u>Capacity</u> (gallons)	<u>Depth</u> (inches)	<u>Capacity</u> (gallons)	
1.00	14	33.00	2,273	65.00	5,131	
2.00	39	34.00	2,365	66.00	5,206	
3.00	71	35.00	2,457	67.00	5,279	
4.00	109	36.00	2,550	68.00	5,351	<--90%
5.00	151	37.00	2,643	69.00	5,420	
6.00	198	38.00	2,737	70.00	5,488	
7.00	249	39.00	2,830	71.00	5,553	
8.00	303	40.00	2,924	72.00	5,615	
9.00	360	41.00	3,018	73.00	5,675	<--95%
10.00	420	42.00	3,111	74.00	5,733	
11.00	483	43.00	3,205	75.00	5,787	
12.00	548	44.00	3,299	76.00	5,837	
13.00	615	45.00	3,392	77.00	5,884	
14.00	685	46.00	3,485	78.00	5,927	
15.00	756	47.00	3,578	79.00	5,965	
16.00	829	48.00	3,671	80.00	5,997	
17.00	905	49.00	3,763	81.00	6,022	
18.00	981	50.00	3,854	82.00	6,035	
19.00	1,060	51.00	3,945			
20.00	1,140	52.00	4,036			
21.00	1,221	53.00	4,126			
22.00	1,303	54.00	4,215			
23.00	1,387	55.00	4,304			
24.00	1,471	56.00	4,391			
25.00	1,557	57.00	4,478			
26.00	1,644	58.00	4,564			
27.00	1,732	59.00	4,649			
28.00	1,820	60.00	4,732			
29.00	1,909	61.00	4,815			
30.00	1,999	62.00	4,896			
31.00	2,090	63.00	4,976			
32.00	2,181	64.00	5,054			