



Model 334 Series Single Poppet Foot Valve & Model 335A Double Poppet Foot Valve

SPECIFICATION SHEET

Application

Installed at the inlet of a suction line normally at the bottom of the storage tank as a prime holding valve.

Features and Details

- Metal to metal seat for long life
- Screen helps filter debris from collecting on the seats

Materials of Construction

- Body and poppet... brass
- Screen... 20 mesh stainless steel
- **335A**— Dual seats provide twice the prime holding capability as single poppet designs

Item Number	A	OD	Height	Weight
334--0100 AV	3/4"	1 5/8"	3 1/32"	1.0
334--0200 AV	1"	2 1/32"	3 33/64"	1.25
334--0300 AV	1 1/2"	2 25/32"	4 3/16"	2.25
334--0400 AV	2"	3 7/16"	5 1/16"	4.75
334BP-0100 AV	1 1/2"	2 25/32"	3 7/8"	2.50
335A--0100 AV	1 1/2"	2 3/4"	5 7/8"	4.50
335A--0200 AV	2"	3 3/8"	6 25/32"	6.50

SPECIFICATION OPTIONS:

A—Thread size (inches)
OD—Outside diameter of valve (inches)
Height—Height of valve (inches)
Weight—Shipping weight (lbs)

