

safety. compliance. reliability.



Notes:

- 1. 8,000 to 12,000 gallon tanks have a center leg which is ¾" shorter than outside legs.
- 2. For 6,000 to 12,000 gallon tanks, leg width varies slightly by manufacturing plant









ConVault

AboveGround Storage Tank Dimensions

Capacity	A	В	C	D	E	F	Approx. Weight
125	4'1-1/8"	4'1-1/8"	3′10″	6"	6"	4'4"	7,300
250	7′8″	3′9″	3′3″	6"	4"	3′9″	8,000
500	11′0″	4′6″	3′4″	6"	4"	3′10″	12,000
1,000	11′0″	5′8″	4'4"	6"	4"	4′10″	18,000
2,000	11′3″	8'0"	5′6″	6"	6"	6"	30,000
3,000	11′3″	8'0"	7′3″	6"	6"	7′9 ½″	37,000
4,000	17"7 ½"	8′0 ½″	6′5 ¾″	6"	6"	6′11 ¾″	45,000
6,000	17"7 ½"	8′0 ½″	8′9 ¾″	Note 2	6"	9'3 ¾"	60,000
8,000	23′1 ½″	8′0 ½″	8′9 ¾″	Note 2	6"	9'3 ¾"	72,000
10,000	28′7 ½″	8′0 ½″	8′9 ¾″	Note 2	6"	9'3 ¾"	89,500
12,000	34′1 ½″	8′0 ½″	8'9 ¾"	Note 2	6"	9'3 ¾"	101,000



